

10/528315
PCT/EP02/12447



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

REC'D 23 DEC 2002

WIPO PCT

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

02021497.9

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

BEST AVAILABLE COPY



Anmeldung Nr:
Application no.: 02021497.9
Demande no:

Anmeldetag:
Date of filing: 26.09.02
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

SIEMENS AKTIENGESELLSCHAFT
Wittelsbacherplatz 2
80333 München
ALLEMAGNE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

Method and apparatus for carrying out diagnosis of a technical installation

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

G01N25/00

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

BEST AVAILABLE COPY

200215750

1

Description

Method and Apparatus for carrying out diagnosis of a technical installation

5

Background of the invention

Predicting and diagnosing of potential failures of technical installations, especially for turbines and/or generators of power plants.

Improving process control is one aim of advanced diagnosis.

State of the Art

15 Different condition monitoring sources are used to enable engine plant assessment, e.g. vibration monitoring of turbines and/or generators.

These, mostly insular, solutions provide data sets (in most cases not compatible to each other, especially if different providers for monitoring equipment are involved) which need to be interpreted for proper condition assessment.

20

Thermography utilises surface temperatures for condition monitoring (where accessible).

25 Thermo-couplers measure selected temperatures for condition monitoring and process control.

Conclusions are drawn from individual measurements.

Embodiments of the invention

30

A combination of thermal information which includes all temperature information.

All acquired measured values of temperatures of the technical installation's components, e.g. surface temperatures of a

35 turbine housing, are stored in e.g. one database (or are linked to each other).

BEST AVAILABLE COPY

2

Occurring and/or occurred failures (and/or other process disturbances) are related to specific temperature patterns derived from a.m. acquired measured values of temperatures; said patterns are constantly being refined.

5

When a particular temperature pattern is detected again, failure prediction can be made.

10 Process disturbances temperature patterns, however, may be distinguished from the ones related to failures and may be utilised for process optimisation and feedback to process enhancement.

Advantages

15

No inhomogeneous data sources for failure prediction and process control.

Limitations of known Thermography and selective temperature measurements are no longer applicable.

20 Cost advantage compared to a combination of conventional condition monitoring systems.

Clear distinction between failure and process disturbance.
Feedback to process control feasible.

25 Figure

The figure illustrates a sample application.

BEST AVAILABLE COPY

200215750

3

Claims

- 5 1. Method for carrying out diagnosis of a technical installation,
characterized in that a failure and/or a process disturbance related to at least one component of the technical
10 installation is assigned at least one temperature pattern which is derived from a number of measured values of temperatures.
- 15 2. Method according to claim 1,
characterized in that said failure and/or process disturbance and its related temperature pattern are stored for a
comparison with an actually occurring temperature pattern during operation of the plant.
- 20 3. Apparatus for carrying out diagnosis of a technical installation,
comprising a first computational unit for assigning at least one temperature pattern which is derived from a number of measured values of temperatures to a failure and/or
25 a process disturbance related to at least one component of the technical installation.
- 30 4. Apparatus according to claim 3,
further comprising a data memory for storing said failure and/or process disturbance and its related temperature pattern.
- 35 5. Apparatus according to claim 4,
further comprising a second computational unit for comparing said stored failure and/or process disturbance and its related temperature pattern with an actually occurring
temperature pattern during operation of the plant.

BEST AVAILABLE COPY

Abstract

Method and Apparatus for carrying out diagnosis of a technical installation


5

According to the invention, a temperature pattern is derived from measured temperature values and assigned at least one failure and/or process disturbance of a technical installation.

10

FIG

BEST AVAILABLE COPY



5 Figure

BEST AVAILABLE COPY